

## NEC AccuSync®AS231WM





## 23" Wide LCD monitor with TN TFT display for office use

- Rapid Response Technology (5 ms)
- Slim bezel design
- Versatile installation (VESA standard), with integrated speakers (1+1 W)
- Low power consumption for reduced Total Cost of Ownership (TCO)
- Ecologics and Ergonomics complying to the latest standards incl. TCO 5.0

## NEC AccuSync®AS231WM

| TN TFT  23.0 / 58.42  0.265  176 horizontal / 170 vertical (typ. at contrast ratio 5:1) 170 horizontal / 160 vertical (typ. at contrast ratio 10:1)  1000:1  250  5  16.7  31.5 - 82.3  56.0 - 75.0  1920 x 1080 at 60 Hz |
|---|
| 0.265 176 horizontal / 170 vertical (typ. at contrast ratio 5:1) 170 horizontal / 160 vertical (typ. at contrast ratio 10:1) 1000:1 250 5 16.7 31.5 - 82.3 56.0 - 75.0  |
| 176 horizontal / 170 vertical (typ. at contrast ratio 5:1) 170 horizontal / 160 vertical (typ. at contrast ratio 10:1) 1000:1 250 5 16.7 31.5 - 82.3 56.0 - 75.0  |
| 170 horizontal / 160 vertical (typ. at contrast ratio 10:1)  1000:1  250  5  16.7  31.5 - 82.3  56.0 - 75.0   |
| 1000:1<br>250<br>5<br>16.7<br>31.5 - 82.3<br>56.0 - 75.0  |
| 250<br>5<br>16.7<br>31.5 - 82.3<br>56.0 - 75.0  |
| 5<br>16.7<br>31.5 - 82.3<br>56.0 - 75.0   |
| 16.7<br>31.5 - 82.3<br>56.0 - 75.0  |
| 31.5 - 82.3<br>56.0 - 75.0  |
| 56.0 - 75.0   |
|   |
| 1920 x 1080 at 60 Hz  |
|   |
| 1920 x 1080; 1680 x 1050; 1440 x 900; 1400 x 1050; 1360 x 768; 1280 x 1024; 1152 x 864;   |
| 1024 x 768; 800 x 600; 720 x 400; 640 x 480   |
| Digital: 1 x DVI-D; Analog: 1 x mini D-sub 15 pin   |
| VESA DDC2Bi   |
| Auto Adjust; Brightness; Colour Control System; Contrast; EcoMode; Expansion Mode; Factory Preset;  |
| Language Select; Monitor Information; On-Screen-Display (OSD) lock-out; OSD Turn Off; Resolution  |
| Notifier; Volume  |
| EPEAT Silver™; CE; TCO 5.0; ERP; TÜV Ergonomics; TÜV GS; GEEA/Energy Label; Energy Star 5.0;  |
| FCC Class B; PCT/Gost; UL/C-UL or CSA; CCC; ISO 9241-307 (pixel failure class I); MPR II/ MPR III   |
| 25 (typ.); 22 (Eco Mode)  |
| < 0.42  |
| 100-120 V/220-240 V; 0.60 A/0.35 A; integrated power supply   |
| +5 to +35   |
| 20 to 80  |
| 100 x 100   |
| -5 to +20   |
| 546.0 x 378.6 x 221.8   |
| 17.0  |
| 5.4   |
| yes   |
| yes   |
| Auto Contrast; Carbon Savings Meter; Rapid Response Technology; Windows 7 compatible  |
| Integrated Speakers (1 W + 1 W)   |
| Black Front Bezel, Black Back Cabinet   |
| Monitor; Power Cable; Signal Cable VGA - VGA; Audio Cable; User Manual  |
| 3 years warranty incl. backlight  |
|   |





















All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All rights reserved. All specifications are subject to change without notice. 05/10